



Toll Free 1-800-378-1965



**TrollPro**® patented design accommodates your **GoPro**® HD Hero4, HD Hero3/3+, and all earlier model HD Hero™ camera and waterproof case. Simply fasten your **GoPro**® camera and waterproof case within the **TrollPro**® using the provided hex bolt and 5/32 hex key tool, attach your desired trolling weight and line and you are ready to go.

- Loosen and remove the hex mounting bolt from the TrollPro camera mount using the 5/32 hex key tool
- After preparing your camera, insert the clear mount tabs on the camera case into TrollPro's camera mount
- Use the hex key tool to align all the holes on the tabs and mount, wiggle the camera to assist in alignment if needed
- Insert the TrollPro hex bolt into the mounting holes and carefully advance the bolt and tighten until fully seated
- Slight downward pressure on the camera case while tightening the bolt may ease tightening

A 32 ounce trolling weight (also available separately) can be attached to the eye hook in front of your **TrollPro**® and can be varied to allow stable camera trolling at various depths and speeds. We generally use the 32 ounce trolling weight when trolling up to 8 knots so the **TrollPro**® will run at a depth of about 3-5 feet at 25-30 feet behind the boat. You will generally be able to see your Short Rigger baits, Teaser, and Flat Lines to your prop wash on the side you are running TrollPro. Run one on each corner to record the whole spread! More weight such as a 42 ounce or 60 ounce trolling weight can be added for faster trolling speeds or deeper camera depth. Downriggers can also be used. See our website for other Tips.

**Use of 200# test or greater trolling wire or cable leader (available separately) is recommended when pulling your TrollPro® where sharp toothed fish such as Barracuda, Wahoo, Shark or King Mackerel may be encountered while trolling, to avoid bite-offs.**

**TrollPro**® can also be attached inside your Teaser Dredge . We just attach a heavy duty “double-snap” swivel to the front eye hook and clip it inside the Dredge, or fasten it along with the 32oz trolling weight in the center of your end dredge.

**Instructions, Tips and Operation Videos on [WWW.TrollPro.com](http://WWW.TrollPro.com) (VIDEOS)**

**Do not operate your TrollPro® deeper than the approved safe operating depth of your GoPro HD Hero camera and waterproof case (190 feet).**



\*Designed for use with GoPro® products. GoPro® is a registered trademark of Woodman Labs, Inc. in the United States and other countries.

